

Mod. R&S. 05/0 Pag. 1/1

Last Updating: 10/2008

# COLORPRINT EXTRA

Digital printing material for difficult fabrics

## Description

Material for thermoresin, ink jet solvent and eco solvent based inks - printing and cutting systems. Suitable for "difficult" fabrics such as nylon jackets, sportswear, bags, umbrellas and leather. **Adhesive** Polyester backing.

#### **Basic Information**

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

Temperature: 165°C

Time: 12-14"
Pressure: min.

### **Application Instructions**

- 1) Print and cut the material
- 2) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
- 3) Weed the exceeding material and remove the image from the backing using the **Siser transparent polyester T.T.D.** (adhesive, transparent polyester, resistant to high temperatures) or other application tapes
- 4) Heat apply
- 5) Remove application tape hot
- 6) If applied onto silicon treated fabrics, we highly recommend to perform both application and washing tests.

#### Suitable for

Polyamide, nylon and silicon treated garments not dyed with sublimation inks

**Washing:** (wait 24h after the heat transfer)

30°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

**Dry-cleaning:** no

Tumble drier: not advisable

N.B.: all information given in this sheet are based on our experience

We recommend to always perform a test before starting standard production

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website <a href="https://www.siser.it">www.siser.it</a>.

For further information, please contact our Sales Office. Thank you.





